

TEST REPORT OF GEAR MOTOR

[ギアモータ試験成績書]

Model
[品名] F2FB-15L-10-S40W

- The values in this test reports are representative values of the motor itself (without a gear head).
- The efficiency of the gear head is not considered.
- この試験成績書は、モータ単体(ギアヘッドなし)での代表特性です。そのため、減速機の効率等は含まれていません。

Specification For Motor [モータ仕様]

Standard code: JIS C 4004

Manufacturer[製造者]	NISSEI CORPORATION		Capacitor (μ F) [コンデンサ]		Start [始動]		
Name [名称]	0.04kW 1 PHASE INDUCTION MOTOR				Run [運転]		2.5
Type [型式]	DS-75	Frequency (Hz) [周波数]	50	60			
Poles [極数]	4	Voltage (V) [電圧]	200	200			
Rating [定格]	S1 CONT.	Current (A) [電流]	0.34	0.33			
Ins. class [絶縁]	B	Rotational Frequency(r/min)[回転速度]	1350	1600			

Characteristics Test [特性試験]

Frequency (Hz) [周波数]	No Load Test [無負荷試験]			Resistance Between at 20 °C (Ω) [端子間抵抗]		
	Voltage(V) [電圧]	Current(A) [電流]	Loss(W) [損失]			
50	200	0.23	35			110
60	200	0.19	37			

Load Characteristics [負荷特性]

Frequency (Hz) [周波数]	Voltage (V) [電圧]	Load (%) [負荷率]	Current (A) [電流]	Rotational Frequency(r/min) [回転速度]	Input (W) [入力]	Break-down Torque(%) [停動トルク]	Locked-rotor Torque(%) [始動トルク]	Starting Current(A) [始動電流]
50	200	25	0.24	1465	40	156	66	0.66
		50	0.25	1435	46			
		75	0.28	1400	53			
		100	0.32	1355	61			
60	200	25	0.23	1755	44	144	68	0.60
		50	0.26	1720	52			
		75	0.29	1680	58			
		100	0.33	1625	66			
		25						
		50						
		75						
		100						
		25						
		50						
		75						
		100						

Temperature Rise Test [温度上昇試験] Frame : Thermometer Method [温度計法]

Frequency(Hz) [周波数]	Voltage(V) [電圧]	Frame(°C) [外被]
50 / 60 / /	200 / 200 / /	46 / 42 / /

- The temperature rise test is the representative property as the gearmotor.
- 温度上昇試験は、ギアモータでの代表特性です。

Insulation Resistance by 500 V Megger 100MΩ
[500Vメガ計による絶縁抵抗]

Withstand Voltage Test 1500 V/min. Withstood
[絶縁耐力試験] [良]

Remarks [注]

NISSEI CORPORATION Anjo Aichi Japan [(株)ニッセイ]	Date of Test [試験日]	Tested by [測定者]	Approved by [承認]
	1999. 5. 6	S.Yamada	K.Amano