

TEST REPORT OF GEAR MOTOR

[ギアモータ試験成績書]

Model

Motor Type

[品名] **F2F15L010-CSBL15WK**

[モータ型式]

DS-75

•The values in this test reports are representative values of the motor itself (without a gear head).
The efficiency of the gear head is not considered.

•この試験成績書は、モータ単体(ギアヘッドなし)での代表特性です。そのため、減速機の効率等は含まれていません。

Specification for Motor [モータ仕様]

Standard code : GB12350, EN60034-1

Manufacturer [製造者]	NISSEI CORPORATION		Capacitor (μF) [コンデンサ]	1.0		
Name [名 称]	0.015kW	Frequency (Hz) [周波数]	50	60		
Phase [相 数]	1	Voltage (V) [電 圧]	200	200		
Poles [極 数]	4	Current (A) [電 流]	0.18	0.17		
Rating [定 格]	S1 CONT.	Rotational Frequency (r/min) [回転速度]	1360	1620		
Ins. class [絶 縁]	E(CCC)B(EN)	P.F. (%) [力 率]	89	97		

Load Characteristics [負荷特性]

Actual Load Method [実負荷法]

Frequency (Hz) [周波数]	Voltage (v) [電圧]	Load (%) [負荷率]	Current (A) [電流]	Rotational Frequency (r/min) [回転速度]	Efficiency (%) [効率]	Power Factor(%) [力率]	Break-down Torque(%) [停動トルク]	Locked-rotor Torque(%) [始動トルク]	Starting Current(A) [始動電流]
50	200	0	0.15	1487	0	66.0	164	64	0.35
		25	0.15	1464	13.6	74.0			
		50	0.16	1440	24.6	79.1			
		75	0.16	1411	32.5	83.7			
		100	0.18	1376	37.3	87.2			
60	200	0	0.10	1789	0	86.6	149	63	0.32
		25	0.11	1760	18.2	92.9			
		50	0.12	1730	31.8	95.8			
		75	0.14	1696	40.5	96.5			
		100	0.16	1653	46.0	96.6			

Temperature Rise Test [温度上昇試験]

Windings: Resistance Method [抵抗法]

Frame: Thermometer Method [温度計法]

Frequency (Hz) [周波数]	Voltage (V) [外被]		Windings (°C) [固定子]	Frame (°C) [外被]
50 / 60 / /	200 / 200 / /		/ / /	31 / 27 / /

•The temperature rise test is the representative property as the gearmotor.

•温度上昇試験は、ギアモータでの代表特性です。

Remark

Insulation Resistance by 500 V Megger 100 MΩ
[500Vメガ計による絶縁抵抗]

Withstand Voltage Test 1500 v / min. Withstood [良]
[絶縁耐力試験]

Nissei Corporation Anjo Aichi Japan [(株)ニッセイ]	Date of Test [試験日]	Tested by [測定者]	Approved by [承認]
	2007.12.10	S.Yamada	K.Amano