

TEST REPORT OF GEAR MOTOR

[ギアモータ試験成績書]

Model

[品名] H2L50R30N-PD22NVTB2

- The values in this test reports are representative values of the motor itself (without a gear head).
The efficiency of the gear head is not considered.
- この試験成績書は、モータ単体(ギアヘッドなし)での代表特性です。そのため、減速機の効率等は含まれていません。

Specification for Motor Part [電動機部仕様]

Standard code : UL1004-1, EN60034-1

Name [名 称]	IPM Motor		
Manufacturer [製造者]	NISSEI CORPORATION		
Capacity [出 力]	2.2kW	Frequency (Hz) [周波数]	50/60
Phase [相 数]	3	Voltage (V) [電 圧]	200~230
Poles [極 数]	6	Current (A) [電 流]	8.20
Rating [定 格]	S1 CONT.	Ins. class [絶 縁]	F

Parameters [パラメータ] at 20°C

Winding Resistance Between Terminals (Ω) [巻線抵抗(端子間)]	0.89
E. M. F Const Between Terminals (mV/r/min) [誘起電圧定数(端子間)]	90.6

Load Characteristics [負荷特性] (For Both 50 Hz And 60 Hz[50,60Hz共通])

Rev. [回転速度]	150r/min		1000r/min		1800r/min	
Load (%) [負荷]	Current (A) [電流]	Input (W) [入力電力]	Current (A) [電流]	Input (W) [入力電力]	Current (A) [電流]	Input (W) [入力電力]
0	1.21	31.4	0.26	52.4	0.35	103.4
25	2.81	81.2	2.20	365.1	2.26	655.83
50	4.51	143.2	4.17	690.7	4.20	1221.3
75	6.31	217.5	6.16	1029.1	6.18	1799.7
100	8.21	304.1	8.18	1380.4	8.20	2391.2

- Current [A] and Input [W] are the values supplied from the inverter to the motor when using Nissei's inverter.
- 電流、入力電力は当社専用インバータを使用した場合のインバータからモータへの入力値です。

Temperature Rise Test [温度上昇試験]

Load (%) [負荷]	Rev. [回転速度]	Hours Run (h) [運転時間]	Stator [固定子]	
			Winding by Resist Method ($^{\circ}\text{C}$) [巻線 (抵抗法)]	Frame by Thermometer Method ($^{\circ}\text{C}$) [フレーム]
100	1800r/min	4	49	32

- The temperature rise test is the representative property as the gearmotor.
- 温度上昇試験は、ギアモータでの代表特性です。

Insulation Resistance by 500V Megger 100M Ω
[500Vメガ計による絶縁抵抗]

Withstand Voltage Test 1500V/min withstood
[絶縁耐力試験] [良]

Remarks [注]

--

NISSEI CORPORATION Anjo Aichi Japan [(株) ニッセイ]	Date of Test [試験日]	Tested by [測定者]	Approved by [承認]
	2019.08.30	Y.Miura	H.Hayashi